POLYURETHANE SELF-STORING AIR ASSEMBLIES (1936)

Applications: These polyurethane assemblies are produced using an ether based resin for better strength, flexibility and superior memory. This hose has excellent resistance to water, chemicals, oxidation, hydrolysis and ozone. It is kink resistant, light weight and mobile.

Color: Blue

Temperature: -40°F to +175°F, -40°C to +79°C

Packaging: Individually Bagged With Header / Display Ready

Fittings: 360° Working Male Pipe Swivels Each End.

Working Pressure:

Dash Size	Actual I.D. (IN.)	Swivel Pipe	Length (FT.)	Working Pressure (P.S.I.)
-4-12	1/4	1/4	12	125
-4-15	1/4	1/4	15	125
-4-25	1/4	1/4	25	125
-4-50	1/4	1/4	50	125
-6-12	3/8	3/8	12	125
-6-15	3/8	3/8	15	125
-6-20	3/8	3/8	20	125
-6-25	3/8	3/8	25	125
-6-50	3/8	3/8	50	125
-6-12B	3/8	1/4	12	125
-6-15B	3/8	1/4	15	125
-6-20B	3/8	1/4	20	125
-6-25B	3/8	1/4	25	125
-6-50B	3/8	1/4	50	125

NOTE: WORKING PRESSURE RATED AT +70°F, +21°C. ANY AMBIENT OR INTERNAL INCREASE IN TEMPERATURE WILL LOWER THE WORKING PRESSURE.

Copyright Fairview Limited 2020