QUALITY RUBBER HOSE (RGP-HOSE)

Applications: This quality rubber hose features EPDM cover and tube with high tensile spiral synthetic yarn reinforcement. It is best suited for applications requiring maximum flexibility or a lighter weight rubber hose.

- **CONSTRUCTION:**
- **TUBE:** EPDM (RMA CLASS C).
- **COVER:** EPDM (RMA CLASS C).
- **REINFORCEMENT:** Spiral synthetic yarn
- **COLORS:** Black, Green, Red, Yellow
- **TEMPERATURE:** -22°F to +167°F, -30°C to +75°C
- **PACKAGING:** Reels
- **FITTINGS:** Hose Barbs
- **BEND PROTECTORS AVAILABLE**

ACCUTEK
Fluid and Air Products

NOTE
WORKING PRESSURE RATED AT +70°F +21°C. ANY AMBIENT OR INTERNAL INCREASE IN TEMPERATURE WILL LOWER THE WORKING PRESSURE.

Dash Size	I.D. (IN.)	O.D. (IN.)	Working Pressure (P.S.I.)	Reel (FT.)
RGP-4	1/4	.500	200	300
RGP-4/2	1/4	.527	250	300
RGP-6	3/8	.669	200	300
RGP-6/2	3/8	.700	250	300
RGP-8	1/2	.810	200	300
RGP-8/2	1/2	.838	250	300
RGP-10	5/8	.930	200	500
RGP-10/2	5/8	.976	250	500
RGP-12	3/4	1.080	200	200
RGP-12/2	3/4	1.141	250	500
RGP-16	1	1.440	200	300
RGP-20	1-1/4	1.750	200	300
RGP-24	1-1/2	2.000	200	300

Copyright Fairview Limited 2020