# Tool Steel Pin Punch

- Made in the USA - Quality and Availability
- Manufactured From Shock Resistant Tool Steel for Unequalled Strength, Toughness, and Durability; Higher Hardness Without Brittleness
- Full Shank Heat Treat is A 2 Step Process Where the Entire Length of the Tool is Hardened and Tempered, Then the Struck End is Drawn Back for to Resist Mushrooming" and "Chipping" Extending the Life of the Tool"
- Pin Area Precision Ground to Prevent Any "Binding" in Work Area
- Modified Parabolic Head Directs the Striking Force to the Center of the Tool for Greater Resistance to "Mushrooming" and "Chipping"
- Black Oxide Finish and Visible "Wear Safety Goggles" Reminder
- Hex Stock Fits More Securely in A Punch & Chisel Holder and Also Reduces the Tendency to Roll on Work Surfaces
- Meets or Exceeds ASME B107.48M and Us Federal Spec. GGG-P-831F




| Cat. No. | UPC No. | Packaging | Point Diameter | Stock Size | Overall Length | Product Weight | Shelf Pack Qty. |
|---|---|---|---|---|---|---|---|
| **70-110** | 781412701104 | Bagged | 1/16 in | 1/4 in | 4.000 in | 0.05 lb | 1 |
| **70-112** | 781412701128 | Bagged | 3/32 in | 5/16 in | 4.500 in | 0.09 lb | 1 |
| **70-114** | 781412701142 | Bagged | 1/8 in | 5/16 in | 4.750 in | 0.08 lb | 1 |
| **70-116** | 781412701166 | Bagged | 5/32 in | 5/16 in | 5.000 in | 0.10 lb | 1 |
| **70-118** | 781412701180 | Bagged | 3/16 in | 3/8 in | 5.250 in | 0.14 lb | 1 |
| **70-120** | 781412701203 | Bagged | 7/32 in | 3/8 in | 5.500 in | 0.16 lb | 1 |
| **70-122** | 781412701227 | Bagged | 1/4 in | 3/8 in | 5.750 in | 0.16 lb | 1 |
| **70-124** | 781412701241 | Bagged | 9/32 in | 3/8 in | 5.750 in | 0.23 lb | 1 |
| **70-126** | 781412701265 | Bagged | 5/16 in | 7/16 in | 6.000 in | 0.24 lb | 1 |
| **70-128** | 781412701289 | Bagged | 3/8 in | 1/2 in | 6.000 in | 0.35 lb | 1 |