



Sta-Plex™ Extreme Pressure Premium Red Grease, 396 Grams

No. 73190 | Item# 1006188 | Case# 1006187

Product Description	A superior multi-purpose certified lithium complex based NLGI #2 grease. Contains extreme pressure, anti-wear, & anti-oxidation additives. Ideal for high temperature & performance applications. Drop point 500°F
Applications	Ind. mining, metal production, machining, plastic molding, pumps, electric motors, ball & roller bearings, kilns, assembly plants, drying ovens, trucks, automobiles, buses, construction equipment, off-road operations, tractors mowers, reapers, water pumps
Unit Package Description	14 Ounce (414 ml) Cartridge
Brand	CRC
Generic Description 1	Premium Red Grease
Net Fill	396 Grams
UPC Code	078254731902
Unit Dimensions	23.65H x 5.41W x 5.41D cm
Units Per Case	10
Case Dimensions	24.13H x 11.43W x 28.9D cm
Cases Per Pallet	150
Case Weight	4.99 kg
I 2 of 5 Code	30078254731903
Appearance	Red Semi-Solid to Solid Grease
Base Type	Lithium Complex
Flash point (F)	475°F
Flash point (C)	246.1°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.9
NLGI Grade	2
Timken OK Load Lbs.	80 Lbs
Plastic Safe	Not Determined

Chemical Solutions to Keep You Moving™
• 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.





Evaporation Rate	Slow
Dielectric Strength	Not Determined
Working Temp (F)	0 to 400°F (300°F continuous)
Working Temp (C)	-17.8 to 204.4°C 149°C continuous)
4 Ball EP	70 LWI; weld point 500+
4 Ball Wear	0.4 typical
Drop Point	260+°C
Elastomer Compatibility	0 to 30% vol; 0 to 15 hard
Leakage	Not Determined
Low Temp Torque	15.5 Max
Oil Separation	5% Typical
Oxidation Stability	Not Determined
Pour Point (F)	5°F
Pour Point (C)	-15°C
ISO Viscosity Grade	220
Water Washout	5% typical
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
Restricted from Sale In:	Not for sale in United States.
Removal (How To)	Remove with a degreaser or brake cleaner product.

Chemical Solutions to Keep You Moving™
• 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.