C.S.A. APPROVED TYPE III PROPANE & NATURAL GAS FORKLIFT & AUTOMOTIVE HOSE ASSEMBLIES (TYPE III CARB ASSY)

Applications: Rubber Covered Stainless Steel Braided Hose With Thermoplastic Liner. For Low Permeation Applications. C.S.A. Approved to C.G.A. Standard 8.1. Used To Conduct Propane In Either A Liquid Or Gaseous State Up To 350 P.S.I.

Temperature Range: -40°F To +200°F (-40°C To 93°C)

EnviroCore™



FS 45° S.A.E. FEMALE FLARE — FS 45° S.A.E. FEMALE FLARE

PART No.	FS	FS	Hose I.D.
III4C__FS4FS4	1/4	1/4	3/16
III6C__FS6FS6	3/8	3/8	5/16
III8C__FS8FS8	1/2	1/2	13/32

NOTE: __ ENTER OVERALL LENGTH IN INCHES FACTORY CRIMP ENDS ONLY.

Ultra Low Emission

C US

LPG/CNG (Type III) UL21 hose. Our CSA / CGA 8.1 Certified hose easily passes CARB permeation requirements of 1.6g/m2-day, this hose can be used virtually anywhere.

CARB

TO BE INSTALLED BY LICENSED GAS FITTERS ONLY.

Copyright Fairview Limited 2020