

Product Family

Miller Scorpion Personal Fall Limiters

An affordable alternative to shock-absorbig lanyards - the lightweight 9-ft web retractable requires less fall clearance.

Visit MillerFallProtection.com >

Honeywell MILLER

Product Numbers & Ordering Information

	Product Numbers	Details
	PFL-1/9FT	**ANSI A10.32 Compliant** Unit Connector: None; Lanyard End Connector: Locking Snap Hook
	PFL-10/9FT	**ANSI A10.32 Compliant** Unit Connector: D-Ring Swivel Hook; Lanyard End Connector: Locking Rebar Hook
	PFL-11/9FT	**ANSI A10.32 Compliant** Unit Connector: Locking Snap Hook and Swivel Shackle; Lanyard End Connector: Locking Rebar Hook
	PFL-12/9FT	**ANSI A10.32 Compliant** Unit Connector: Carabiner and Swivel Shackle; Lanyard End Connector: Locking Rebar Swivel Hook
	PFL-13/9FT	**ANSI A10.32 Compliant** Unit Connector: D-Ring Swivel Hook; Lanyard End Connector: Locking Rebar Swivel Hook
	PFL-14/9FT	**ANSI A10.32 Compliant** Unit Connector: Locking Snap Hook and Swivel Shackle; Lanyard End Connector: Locking Swivel Snap Hook
	PFL-15/9FT	**ANSI A10.32 Compliant** Unit Connector: None; Lanyard End Connector: Locking Swivel Snap Hook

© Honeywell International Inc.

	PFL-15-Z7/9FT	**ANSI Z359 Compliant** Unit Connector: None; Lanyard End Connector: Locking Swivel Snap Hook
	PFL-16/6FT	**ANSI A10.32 Compliant** Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Swivel Snap Hook - 6ft
	PFL-16/9FT	**ANSI A10.32 Compliant** Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Swivel Snap Hook
	PFL-17/9FT	**ANSI A10.32 Compliant** Unit Connector: None; Lanyard End Connector: Web Loop for Carabiner
	PFL-1-Z7/9FT	**ANSI Z359 Compliant** Unit Connector: None; Lanyard End Connector: Locking Snap Hook
	PFL-2/9FT	**ANSI A10.32 Compliant** Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Snap Hook
	PFL-2-Z7/9FT	**ANSI Z359 Compliant** Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Snap Hook
	PFL-3/9FT	**ANSI A10.32 Compliant** Unit Connector: Stainless Steel Swivel Shackle; Lanyard End Connector: Locking Snap Hook
	PFL-3-Z7/9FT	**ANSI Z359 Compliant** Unit Connector: Stainless Steel Swivel Shackle; Lanyard End Connector: Locking Snap Hook
	PFL-4/9FT	**ANSI A10.32 Compliant** Unit Connector: Carabiner and Swivel Shackle; Lanyard End Connector: Locking Snap Hook
	PFL400#-11/9FT	**ANSI A10.32 Compliant** Unit Connector: Locking Snap Hook and Swivel Shackle; Lanyard End Connector: Locking Rebar Hook - 400 lbs. Capacity
	PFL400#-12/9FT	**ANSI A10.32 Compliant** Unit Connector: Carabiner and Swivel Shackle; Lanyard End Connector: Locking Rebar Swivel Hook - 400 lbs. Capacity
	PFL400#-14/9FT	**ANSI A10.32 Compliant** Unit Connector: Locking Snap Hook and Swivel Shackle; Lanyard End Connector: Locking Swivel Snap Hook - 400 lbs. Capacity

© Honeywell International Inc.

	PFL400#-15/9FT	**ANSI A10.32 Compliant** Unit Connector: None; Lanyard End Connector: Locking Swivel Snap Hook - 400 lbs. Capacity
	PFL400#-16/9FT	**ANSI A10.32 Compliant** Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Swivel Snap Hook - 400 lbs. Capacity
	PFL400#-16-Z7/9FT	**ANSI Z359 Compliant** Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Swivel Snap Hook - 400 lbs. Capacity
	PFL400#-2/9FT	**ANSI A10.32 Compliant** Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Snap Hook - 400 lbs. Capacity
	PFL400#-3/9FT	**ANSI A10.32 Compliant** Unit Connector: Stainless Steel Swivel Shackle; Lanyard End Connector: Locking Snap Hook - 400 lbs. Capacity
	PFL400#-4/7FT	**ANSI A10.32 Compliant** Unit Connector: Carabiner and Swivel Shackle; Lanyard End Connector: Locking Snap Hook - 7ft - 400 lbs. Capacity
	PFL400#-4/9FT	**ANSI A10.32 Compliant** Unit Connector: Carabiner and Swivel Shackle; Lanyard End Connector: Locking Snap Hook - 400 lbs. Capacity
	PFL400#-5/9FT	**ANSI A10.32 Compliant** Unit Connector: D-Ring Swivel Hook; Lanyard End Connector: Locking Snap Hook - 400 lbs. Capacity
	PFL400#-6/9FT	**ANSI A10.32 Compliant** Unit Connector: Rebar Hook and Swivel Shackle; Lanyard End Connector: Locking Snap Hook - 400 lbs. Capacity
	PFL400#-7/9FT	**ANSI A10.32 Compliant** Unit Connector: Locking Snap Hook and Swivel Shackle; Lanyard End Connector: Locking Snap Hook - 400 lbs. Capacity
	PFL400#-8/9FT	**ANSI A10.32 Compliant** Unit Connector: Captive-Eye Carabiner; Lanyard End Connector: Locking Snap Hook - 400 lbs. Capacity
	PFL400#-9/9FT	**ANSI A10.32 Compliant** Unit Connector: Carabiner and Swivel Shackle; Lanyard End Connector: Locking Rebar Hook - 400 lbs. Capacity
	PFL-4-Z7/9FT	**ANSI Z359 Compliant** Unit Connector: Carabiner and Swivel Shackle; Lanyard End Connector: Locking Snap Hook

© Honeywell International Inc.

	PFL-5/9FT	**ANSI A10.32 Compliant** Unit Connector: D-Ring Swivel Hook; Lanyard End Connector: Locking Snap Hook
	PFL-6/9FT	**ANSI A10.32 Compliant** Unit Connector: Rebar Hook and Swivel Shackle; Lanyard End Connector: Locking Snap Hook
	PFL-6-Z7/9FT	**ANSI Z359 Compliant** Unit Connector: Rebar Hook and Swivel Shackle; Lanyard End Connector: Locking Snap Hook
	PFL-7/9FT	**ANSI A10.32 Compliant** Unit Connector: Locking Snap Hook and Swivel Shackle; Lanyard End Connector: Locking Snap Hook
	PFL-7-Z7/9FT	**ANSI Z359 Compliant** Unit Connector: Locking Snap Hook and Swivel Shackle; Lanyard End Connector: Locking Snap Hook
	PFL-8/9FT	**ANSI A10.32 Compliant** Unit Connector: Captive-Eye Carabiner; Lanyard End Connector: Locking Snap Hook
	PFL-9/9FT	**ANSI A10.32 Compliant** Unit Connector: Carabiner and Swivel Shackle; Lanyard End Connector: Locking Rebar Hook
	PFL-9-Z7/9FT	**ANSI Z359 Compliant** Unit Connector: Carabiner and Swivel Shackle; Lanyard End Connector: Locking Rebar Hook
	PFL-18-Z7/9FT	**Aluminum; ANSI Z359 Compliant** Unit Connector: Aluminum Carabiner and Swivel Shackle; Lanyard End Connector: Aluminum Locking Snap Hook
	PFL-19-Z7/9FT	**Aluminum; ANSI Z359 Compliant** Unit Connector: Aluminum Locking Rebar Hook and Swivel Shackle; Lanyard End Connector: Aluminum Locking Snap Hook
	PFL-20-Z7/9FT	**Aluminum; ANSI Z359 Compliant** Unit Connector: Aluminum Locking Snap Hook and Swivel Shackle; Lanyard End Connector: Aluminum Locking Snap Hook
	PFL-21-Z7/9FT	**Aluminum; ANSI Z359 Compliant** Unit Connector: Aluminum Locking Snap Hook and Swivel Shackle; Lanyard End Connector: Aluminum Locking Rebar Hook

Overview

Key Features

- Greater versatility through dual operation:

© Honeywell International Inc.

– attach directly to the harness D-ring for use as a personal fall limiter, or
– use as a traditional retractable lifeline

- Small, lightweight design 2.9 lbs. (1.3kg)
- Quick-activating, high-strength stainless steel braking system – arrests free falls
- Variety of integral anchorage connectors available
- 400 lbs. (181.4kg) capacity models available upon request
- No annual factory recertification required
- Visual load indicator – indicates the unit must be removed from service

Recommended Industries/Use

- Construction
- Municipal Services
- Transportation

Hazards

- Confined Space
- Fall from height

Regulations

- Meets all applicable OSHA, ANSI and CSA standards

Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

Specifications

Specification Sheets

- For full engineering specification sheets, go to the spec sheet section under downloads and documentation

Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

Additional Information

800/873-5242 or email: hsptechsupport@honeywell.com

Technical Support

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: millertechexpert@sperianprotection.com

© Honeywell International Inc.

© Honeywell International Inc.