

Product Family

North Anchor Slings

Honeywell NORTH

Product Numbers & Ordering Information

	Product Numbers	Details
	FP02/3	**PVC Coated Steel Anchor Sling** 1/4" (6mm) galvanized steel cable with swaged eyes at each end. PVC coated against corrosion - 3'
	FP02/4	**PVC Coated Steel Anchor Sling** 1/4" (6mm) galvanized steel cable with swaged eyes at each end. PVC coated against corrosion - 4'
	FP02/4F	**PVC Coated Steel Anchor Sling - Flemish Eye** 1/4" (6mm) galvanized steel cable with Flemish eyes, swaged at each end. PVC coated against corrosion. 1.2m (4')
	FP02/6	**PVC Coated Steel Anchor Sling** 1/4" (6mm) galvanized steel cable with swaged eyes at each end. PVC coated against corrosion. 1.8m (6')
	FP02/6F	**PVC Coated Steel Anchor Sling - Flemish Eye** 1/4" (6mm) galvanized steel cable with Flemish eyes, swaged at each end. PVC coated against corrosion. 1.6m (4')
	FP02/8	**PVC Coated Steel Anchor Sling** 1/4" (6mm) galvanized steel cable with swaged eyes at each end. PVC coated against corrosion - 8'
	FP03/2	**Pass-Through Anchor Sling** 2" (50 mm) heavy-duty nylon web with small D-ring which passes through the large D-ring to form loop around anchor - 2'

© Honeywell International Inc.

	FP03/3	**Pass-Through Anchor Sling** 2" (50 mm) heavy-duty nylon web with small D-ring which passes through the large D-ring to form loop around anchor - 3'
	FP03/4	**Pass-Through Anchor Sling** 2" (50 mm) heavy-duty nylon web with small D-ring which passes through the large D-ring to form loop around anchor - 4'
	FP03/6	**Pass-Through Anchor Sling** 2" (50 mm) heavy-duty nylon web with small D-ring which passes through the large D-ring to form loop around anchor - 6'
	FP04/3	**Cross-Arm Anchorage Sling** 1" (25mm) heavy duty nylon web with large D-ring which passes through the loop to choke around anchor - 3'
	FP04/4	**Cross-Arm Anchorage Sling** 1" (25mm) heavy duty nylon web with large D-ring which passes through the loop to choke around anchor - 4'
	FP04/6	**Cross-Arm Anchorage Sling** 1" (25mm) heavy duty nylon web with large D-ring which passes through the loop to choke around anchor - 6'
	FP242/2	**Tiny N Tough Dyneema Sling** Made of revolutionary Dyneema webbing for lightweight, small size and exceptional strength - 3/4" (19 mm) web can be used without additional protective materials in concrete forming - 2'
	FP242/4	**Tiny N Tough Dyneema Sling** Made of revolutionary Dyneema webbing for lightweight, small size and exceptional strength - 3/4" (19 mm) web can be used without additional protective materials in concrete forming - 4'
	FP242/6	**Tiny N Tough Dyneema Sling** Made of revolutionary Dyneema webbing for lightweight, small size and exceptional strength - 3/4" (19 mm) web can be used without additional protective materials in concrete forming - 6'

Additional Information

1-888-212-SAFE (7233)

Overview

Key Features

North Anchor slings are easy to use, high strength anchorage connectors. They provide you with an anchorage connector that can be used almost anywhere an anchorage point is needed.

Recommended Industries/Use

- Construction
- Manufacturing
- Utilities

Hazards

- Fall from height

Regulations

- Regulations - ANSI Z359.1

© Honeywell International Inc.

- Regulations - OSHA

Specifications

Minimum Breaking Strength

- 5,000 lbs (22.2 kN)

Training & Proper Use

See Operating and Maintenance Instruction Manual for details.

Technical Support

1.800.873.5242 or hsptechinfocan@honeywell.com

© Honeywell International Inc.

© Honeywell International Inc.