PYRAMEX

Ever-Lite® ANSI • CE • CSA •



SB86

RUBBER NOSEPIECE | CO-INJECTED TEMPLES | READER OPTION

Soft nosepiece for snug fit // Slim co-injected temples // Lightweight spectacle – 22 gm // Custom imprinting available

WATCH THE EVER-LITE VIDEO

Black Frame | 17 Variations

SB8610D	Clear	
SB8610DT	Clear H2X AF	
SB8610DTM	Clear H2MAX AF	
SB8620D	Gray	
SB8620DT	Gray H2X AF	
SB8620DTM	Gray H2MAX AF	
SB8623D	Dark Gray	
SB8623DT	Dark Gray H2X AF	
SB8624D	Photochromic	
SB8625DTM	Light Gray H2MAX AF	
SB8630D	Amber	
SB8660D	Infinity Blue	
SB8660DT	Infinity Blue H2X AF	
SB8660DTM	Infinity Blue H2MAX AF	
SB8665D	Ice Blue Mirror	
SB8680D	I/O Mirror	
SB8680DT	I/O Mirror AF	

Black and Lime Frame | 2 Variations

SBL8610DTM	Clear H2MAX AF
SBL8620DTM	Gray H2MAX AF



Photochromic lenses change from clear to dark after exposure to direct UV light. Lenses change from dark to clear after removal from UV light.

Ever-Lite® Readers ANSI • CSA •



RUBBER NOSEPIECE | CO-INJECTED TEMPLES | READER OPTION

Soft nosepiece for snug fit // Slim co-injected temples // Lightweight spectacle – 22 gm // Custom imprinting available

Black Frame | 14 Variations

SB8610R15	Clear	+1.5 Mag
SB8610R15TM	Clear H2MAX AF	+1.5 Mag
SB8610R20	Clear	+2.0 Mag
SB8610R20TM	Clear H2MAX AF	+2.0 Mag
SB8610R25	Clear	+2.5 Mag
SB8610R25TM	Clear H2MAX AF	+2.5 Mag
SB8610R30	Clear	+3.0 Mag
SB8610R30TM	Clear H2MAX AF	+3.0 Mag
SB8620R15	Gray	+1.5 Mag
SB8620R15TM	Gray H2MAX AF	+1.5 Mag
SB8620R20	Gray	+2.0 Mag
SB8620R20TM	Gray H2MAX AF	+2.0 Mag
SB8620R25	Gray	+2.5 Mag
SB8620R25TM	Gray H2MAX AF	+2.5 Mag

Ever-Lite®

General Specifications

Weight: 22 gm

PD: 64 mm

Bridge: 11.2 mm

Lens base: 8 curve

Lens size diagonal: 79.6 mm

Lens size vertical: 43.3 mm

Lens thickness: 1.8 mm

Overall length (lens - tip): 163.5 mm

Overall width (hinge - hinge): 134.3 mm

Closest point between temple tips: 70 mm

Closest point between lens: 11 mm

Materials

Lens: polycarbonate

Frame: polycarbonate

Temples: polycarbonate & thermoplastic elastomers (TPE)

Hinge: polycarbonate

Screw: stainless steel

Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SB8610D	P + U6	P Z87 + / P c SEI Z94.3
SB8610DT	P + U6	P Z87 + / P c SEI Z94.3
SB8610DTM	P + U6 X	P Z87 + / P c SEI Z94.3
SB8620D	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB8620DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB8620DTM	P + U6 L2.5 X	P Z87 + / P c SEI Z94.3
SB8623D	P + S	P Z87 + / P c SEI Z94.3
SB8623DT	P + S	P Z87 + / P c SEI Z94.3
SB8624D	P + S	P Z87 + / P c SEI Z94.3
SB8625DTM	P + S X	P Z87 + / P c SEI Z94.3
SB8630D	P + U6	P Z87 + / P c SEI Z94.3
SB8660D	P + S	P Z87 + / P c SEI Z94.3
SB8660DT	P + S	P Z87 + / P c SEI Z94.3
SB8660DTM	P + S X	P Z87 + / P c SEI Z94.3
SB8665D	P + S	P Z87 + / P c SEI Z94.3
SB8680D	P + U6 L1.7	P Z87 + / P c SEI Z94.3
SB8680DT	P + U6 L1.7	P Z87 + / P c SEI Z94.3
SBL8610DTM	P + U6 X	P Z87 + / P c SEI Z94.3
SBL8620DTM	P + U6 L2.5 X	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special Purpose

W: Welding filter

X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Ever-Lite Readers

General Specifications

Weight: 22 gm

PD: 64 mm

Bridge: 11.2 mm

Lens base: 8 curve

Lens size diagonal: 79.6 mm

Lens size vertical: 43.3 mm

Lens thickness: 1.8 mm

Overall length (lens - tip): 163.5 mm

Overall width (hinge - hinge): 134.3 mm

Closest point between temple tips: 70 mm

Closest point between lens: 11 mm

Materials

Lens: polycarbonate

Frame: polycarbonate

Temples: polycarbonate & thermoplastic elastomers (TPE)

Hinge: polycarbonate

Screw: stainless steel

Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking	
SB8610R15	P + U6	+1.50	P Z87 + / P c SEI Z94.3
SB8610R15TM	P + U6 X	+1.50	P Z87 + / P c SEI Z94.3
SB8610R20	P + U6	+2.00	P Z87 + / P c SEI Z94.3
SB8610R20TM	P + U6 X	+2.00	P Z87 + / P c SEI Z94.3
SB8610R25	P + U6	+2.50	P Z87 + / P c SEI Z94.3
SB8610R25TM	P + U6 X	+2.50	P Z87 + / P c SEI Z94.3
SB8610R30	P + U6	+3.00	P Z87 + / P c SEI Z94.3
SB8610R30TM	P + U6 X	+3.00	P Z87 + / P c SEI Z94.3
SB8620R15	P + U6 L2.5	+1.50	P Z87 + / P c SEI Z94.3
SB8620R15TM	P + U6 L2.5 X	+1.50	P Z87 + / P c SEI Z94.3
SB8620R20	P + U6 L2.5	+2.00	P Z87 + / P c SEI Z94.3
SB8620R20TM	P + U6 L2.5 X	+2.00	P Z87 + / P c SEI Z94.3
SB8620R25	P + U6 L2.5	+2.50	P Z87 + / P c SEI Z94.3
SB8620R25TM	P + U6 L2.5 X	+2.50	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark

+: High impact

S: Special purpose

X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L2.5: 29% max visible light

Temple Marking Symbols

+1.50: magnification of +1.5

+2.00: magnification of +2.0

+2.50: magnification of +2.5

+3.00: magnification of +3.0

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices