Atrex™ ANSI • CSA •

FOAM PADDING | CO-INJECTED TEMPLES | RUBBER NOSEPIECE

Foam padding // Built-in rubber nosepiece // Co-injected temples



Black Frame | 3 Variations

- SB10810DT •• Clear AF
- SB10820DT •• Gray AF
- SB10880DT •• I/O Mirror AF

Pearl Gray Frame | 1 Variation

- SPG10810DT •• Clear AF

Translucent Brown Frame | 1 Variation

- STB10815DT •• Coffee AF

Red Frame | 1 Variation

- SR10870D •• Silver Mirror

Restraining Strap

108STRAP

SPG108

SR108

STB108

Part No.	Lens Marking	Temple Marking
SB10810DT	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB10820DT	P Z87 + U6 L3	P Z87 + / P c SEI Z94.3
SB10880DT	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SPG10810DT	P Z87 + U6	P Z87 + / P c SEI Z94.3
SR10870D	P Z87 + S	P Z87 + / P c SEI Z94.3
STB10815DT	P Z87 + U6 L3	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special Purpose

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

L3: 18% Max. Visible Light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices

General Specifications

Weight: 34.22 gm

PD: 64 mm

Bridge: 16 mm

Lens base: 8 curve

Lens size diagonal: 63 mm

Lens size vertical: 37.5 mm

Lens thickness: 2.0 mm

Overall length (lens - tip): 166 mm

Overall width (screw - screw): 136.3 mm

Materials

Lens: polycarbonate

Frame: polycarbonate & foam

Temples: polycarbonate & thermoplastic elastomers (TPE)

Nosepiece: thermoplastic rubbers (TPR)