Scotch® Fire-Retardant Electric Arc Proofing Tape 77 Series

Data Sheet

Description

Scotch® Fire-Retardant Electric Arc Proofing Tape 77 Series are designed to protect most types of electrical cables from fault arc-generated heat and flames of nearby cable failures. These halogen-containing elastomeric tapes are formulated to generate a thick, insulating charred buildup when exposed to high temperatures. The insulating charred buildup protects wrapped cables and cable accessories from the fault arc-generated heat and flames of cable failures within approximately 20 inches until limiting devices can interrupt the faulted circuit.

Because Scotch® Fire-Retardant Electric Arc Proofing Tape 77 Series are elastomeric and unsupported, they are very conformable. Installers can provide virtually wrinkle-free coverage of cables and irregularly-shaped cable accessories, easily and rapidly. This exceptional conformability provides better product control while wrapping and yields more uniform coverage. Also, the tape's thin cross section reduces the overall weight compared to other methods while providing arc protection. The white gray color of Scotch® Tape 77 White allows for easy identification of burned areas.

One half-lap wrap provides adequate protection for most installations. However, additional wraps can be applied, if conditions warrant, without requiring a reduction in conductor loads.

Features

- Flexible unsupported elastomer makes it easy to apply and remove for cable inspection.
- Conformability provides virtually wrinkle-free wrapping and complete coverage with minimal effort.
- Provides fault arc protection to adjacent wrapped cables and cable accessories.
- Self-extinguishing; will not support combustion.
- Thin cross section 30 mils thickness saves space and allows cable heat to dissipated.
- Will last and maintain its arc proofing properties for the life of the cable. Resistant to water, salt water, acids, sewage and ultraviolet light.
- Can be removed and reused.
- Standard roll sizes for fast convenient installation.
- White-gray color of Scotch® Tape 77 White allows for the easy identification of fire damage areas.

Applications

- To arc proof high-energy power cables that may be exposed to arc-fault generated heat and flames from nearby failures of other high-energy cables (any cables within 20 inches are considered to be exposed)
- To arc proof control cable when high energy power cables are present
- To provide additional electrical insulation, thus reducing possibilities of transferred arcs.

Typical Properties

Not for specifications. Values are typical, not to be considered minimum or maximum. Properties measured at room temperature 73°F (23°C) unless otherwise stated.

Physical Properties (ASTM D1000 unless noted)	**Typical Value** US units (metric)	
Product Number	77 Black	77 White
Color	Black	White-Gray
Total Thickness	.030 inches (0,76 mm)	
Breaking Strength	1200 psi (8,3 MPa)	
Elongation (% at break) 23°C -12°C -18°C	 150% 130% 90%	
Flame Resistant (UL 94 [Self-extinguishing])	V-O	
Oxygen Index (ASTM D2863)	26 - 28 %	
Flame Test (Consolidated Edison EO 5343 Sec 3.2.6)	Pass	

Electrical & Thermal Properties	**Typical Value** US units (metric)
Dielectric Breakdown	> 10,000V
Thermal Conductivity (23°C) ASTM C518	0.15 BTU-ft (0,25 W/mk) ft^2-hr-°F

Product Specifications

Scotch® Electric Arc Proofing Tape 77 Series shall consist of a flexible, conformable, unsupported intumescent elastomer. The tape shall be 0.030 inches thick and be capable of over 100% elongation. The tape shall be non-corrosive to metallic cable sheaths and compatible with synthetic cable jackets (i.e. semiconducting URD type, polyethylene, PVC, etc.). It shall be self-extinguishing and shall not support combustion. The tape is resistant to water, salt water, gases, and sewage.

Engineering and Architectural Specification

High-energy cable, important communication and control cables in manholes, vaults, on open cable trays or other exposed locations where threat of fault can occur, shall be arc proofed with one half-lapped layer of Scotch® Fire-Retardant Electric Arc Proofing Tape 77 Black or 77 White.

Installation Technique

Wrap Scotch® Tape 77 Black or 77 White in half-lapped layers. The tape should be stretched slightly to obtain a snug, virtually wrinkle-free wrap which conforms to the cable. Overlap the last 6 inches of protected cable when starting a new roll of tape.

Since the Scotch® Tape 77 Series is not adhesive coated, it must be held in place after wrapping with bands of Scotch® Glass Cloth Electrical Tape 69. The most effective and economical way to hold either of these tapes in place is by banding (2 complete wraps) the first and last applied wrap.

Shelf Life & Storage This product has a 5-year shelf life from date of manufacture when stored in a humidity-controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity).

Availability Please contact your local distributor; available from 3M.com/electrical [Where to Buy] or call 1.800.676.8381.

Coverage Table

Cable O.D. (inches)	Tape Width (inches)	Number of 20 foot rolls needed to cover 100 feet of cable with one-half lap wrap (rolls)
1”	1 ½”	21
1 ¼”	1 ½”	27
1 ½”	1 ½”	32
1 ¾”	3”	19
2”	3’	20
2 ¼”	3”	24
2 ½”	3”	27
2 ¾”	3”	29
3”	3”	32
3 ½”	3”	37
4”	3”	42
4 ½”	3”	48

Use this formula to determine the quantity of Scotch® Tape 77 required to cover cables with a half-lap wrap: C =

Circumference (C = πD)
π = 3.14
Cable O.D. in Inches

LC = Length of Cable in Inches
W = width of Tape in Inches (minus ½ tape width) D =
LT = Length of Tape in Inches

$$\frac{(C)\,(LC)}{(LT)\,(W)} = \text{Number of Rolls Required}$$

TECHNICAL STATEMENT

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (*e.g.*, OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com

3M and Scotch are trademarks of 3M Company.

3M
Electrical Markets Division
13011 McCallen Pass, Bldg. C
Austin, TX 78753
Phone: 800.245.3573
www.3M.com/electrical

Please Recycle. Printed in USA
© 3M 2021. All Rights Reserved.
78-8124-5426-8 Rev G