TenActiv™ | S15TAFGPU

Low-linting gloves to prevent contamination with incidental cut protection and tactile dry grip





ANSI/ISEA 105
A3
3 3

ABOUT THE PRODUCT

Our TenActiv™ S15TAFGPU low-linting gloves offer low cut protection to protect hands from incidental cut hazards. TenActiv™ engineered yarn provides 360° cut protection with ANSI A3 cut resistance, plus a polyurethane palm coating for steady dry grip and tactile feel. They're low-linting to avoid shedding material and prevent contamination.

APPLICATIONS

AUTOMOTIVE, CONSTRUCTION, GLASS MANUFACTURING, UTILITIES

RECOMMENDED FOR

ASSEMBLY, GLASS HANDLING, HVAC, MATERIAL HANDLING

AVAILABLE SIZING

5, 6, 7, 8, 9, 10, 11, 12

SHIPPING AND PACKAGING

Unit of Measure	Pair
Country of Origin	Malaysia

FEATURES AND TECH

Extended Sizes	Yes
Low-Linting	Yes

LAUNDERING INSTRUCTIONS

Wash & Tumble Dry Low Heat

PROP 65

WARNING: Known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

USA, Canada, Mexico Sales
business.development@superiorglove.com
800-265-7617 / 519-853-1920

International Sales
international@superiorglove.com
Date printed: 10/23/2025

superiorglove

English