#S13SXGNT

Superior Touch®

Cut-Resistant 13-Gauge Knit with Dyneema®, Nitrile Palms



#S13SXGNT

Dyneema®
The softer strength

ASTM ANSI PUNCTURE 3

ASTM ANSI ABRASION 4

ASTM ANSI CUT LEVEL 2

515 grams of cut protection.

FEATURES

- Lint-free, continuous filament yarn
- Unparalleled cut resistance
- Rated ASTM cut-level 2
- Rated ASTM puncture-level 3
- High dexterity and flexibility

APPLICATIONS

Sharp Steel HVAC
Glass Metal Fabrication
Circuit Boards Automotive
Food Handling

Dyneema® is 15 times stronger than steel on an equal weight basis and twice as strong as Kevlar®. It is also a lint-free, continuous filament yarn. With their high coefficient of friction, nitrile palm coating and Dyneema® glove body, these gloves give an unparalleled cut resistance for a glove of such high dexterity and flexibility. A good choice for handling sharp steel, glass or circuit boards, especially when lint and particulate contamination is a concern. CFIA Approved for food handling.

For more information on gloves made with Dyneema® click the following link:
http://www.superiorglove.com/work-gloves/cut-resistantgloves/dyneema-cut-resistant-gloves

Dyneema® is a registered trademark of Royal DSM N.V.

AVAILABLE SIZES

6 7 8 9 10 11

Canadian Office and Factory
Acton, Ontario Canada
1-800-265-7617 | customerservice@superiorglove.com

US Factory and Warehouse
Buffalo, New York USA

European Office
+44 (0) 7748 801 833 | graham.ayers@superiorglove.com
superiorglove.com

superiorglove®