Primary Wire



GPT Wire

Techspan GPT (General Purpose Thermoplastic) primary single conductor wire is manufactured using 100% pure copper conductors with a PVC compound that resists chemical, abrasion and heat, up to 85°C (185°F). Jacket surface is smooth enough for easy, clean wire stripping. Ideal for automotive, truck, trailers, tractor, boats, and other point-to-point, low voltage applications (up to 60 Volts). Type GPT to SAE specification J1128 meets the standard for OEM or replacement applications for general purpose requirements.

Mini Spools

GA	Length		O.D.	Stranding	Black	Blue	Brown	Green	Red	White	Yellow
18	50'	(15.2m)	.091"	16 x 30 x .010"	668051	668052	668053	668054	668056	668057	668059
16	35'	(10.7m)	.104"	19 x 29 x .011"	668061	668062	668063	668064	668065	668066	668067
14	25'	(7.6m)	.119"	19 x 27 x .014"	668068	668069	668070	668071	668072	668073	668074
12	15'	(4.6m)	.145"	19 x 25 x .018"	668075	668076	668983	668922	668077	668078	668928
10	10'	(3m)	.175"	19 x 23 x .024"	668080	668906	668081	668980	668082	668981	668979

O.D. = Outside Diameter

100' (30.5m) Spools

GA	O.D.	Stranding	Black	Blue	Brown	Green	Red	White	Yellow	Grey	Orange	Pink	Purple	Tan	
20	.084"	7 x 30 x .012"	767987	768988	767989	767990	767991	767992	767993	*767996	*767995		*767997		*NEW
18	.091"	16 x 30 x .010"	768000	768001	768002	768003	768005	768006	768007	768009	768004	*767994	768008	*767999	*NEW
16	.104"	19 x 29 x .011"	768010	768011	768012	768013	768015	768016	768017	768019	768014		768018		
14	.119"	19 x 27 x .014"	768020	768021	768022	768023	768025	768026	768027	768029	768024	*767984	768028		*NEW
12	.145"	19 x 25 x .018"	768030	768031	768032	768033	768035	768036	768037		768034				
10**	.175"	19 x 23 x .024"	768102	768103	768104	768105	768106	768107	768108						
8	.216"	19 x 21 x .028"	768050				768155	768056							
6	.285"	7 x 19 x .014"	768060				768165								
4	.354"	7 x 27 x .014"					768175								

O.D. = Outside Diameter
Note: 8GA to 4GA supplied on metal spools
** 50' (15.2 m) spools

1000' (305 m) Spools

GA	O.D.	Stranding	Black	Blue	Brown	Green	Red	White	Yellow	Grey	Orange	Purple	
20	.084"	7 x 30 x .012"	*767987M	*767988M	*767989M	*767990M	*767991M	*767992M	*767993M				*NEW
18	.091"	16 x 30 x .010"	768200	768201	768202	768203	768205	768206	768207	768209	768204	768208	
16	.104"	19 x 29 x .011"	768210	768211	768212	768213	768215	768216	768217	768219	768214	768218	
14	.119"	19 x 27 x .014"	768220	768221	768222	768223	768225	768226	768227	768229	768224	768228	
12	.145"	19 x 25 x .018"	768230	768231	768232	768233	768235	768236	768237		768234		
10	.175"	19 x 23 x .024"	768240	768241	768242	768243	768245	768246	768247				
8	.216"	19 x 21 x .028"	*768250				*768255	*768256					*NEW

O.D. = Outside Diameter
Note: 1000' spools supplied on metal spools.

LOOKING FOR STRIPED WIRE?
Contact Techspan for availability. Minimum Order Quantities will apply.

