THE FIREWALL FR® COMMITMENT

Viking® Firewall FR® is committed to providing industry leading Flame Resistant garments that offer the highest level of safety for workers exposed to electrical arc an hydrocarbon flash fire hazards.

Viking® Firewall FR® has partnered with Westex® by Milliken® to supply best-in-class inherent and treated flame-resistant fabrics for Viking Firewall FR® FR garment. Milliken & Company, with the recent acquisition of Westex®, is the largest flame resistant fabric manufacturer in the world and a market leader in innovation and technology.

Fabric Choices for All Industry Applications

Viking® Firewall FR® garments are offered in inherent or treated flame-resistant fabrics by Westex® by Milliken.®. Westex® by Milliken ® treated FR fabric® is made of 88% cotton, 12% nylon blend with a proprietary permanent FR treatment process guaranteed for the life of the garment. Westex® CXP® flame-resistant fabric, made of Nomex® IIIA fibres, offers greater comfort and durability than other Nomex® IIIA fabrics. Nomex® CXP® combines the Softouch Technology™ process with Leap® technology to provide a soft Nomex® fabric that protects against both arc flash and flash fire hazards.

Westex® by Milliken® Flame Resistant Fabrics

Westex® by Milliken® 88% cotton / 12% Nylon are high performance flame-resistant (FR) fabrics specifically designed for industrial workwear. The proprietary fabrics use a specialized ammonia-free FR treatment process and are constructed of an optimized blend of Pima cotton and high-tenacity Nylon designed to help mitigate potential injuries due to electric arc and flash fire exposure, while providing enhanced durability and comfort. The combination of these capabilities makes it an ideal fabric for industrial workwear occupations in manufacturing, utilities, electrical maintenance, petrochemical, welding, and steel.

Westex® by Milliken®'s excellent protection against Flash Fire and Arc Flash can significantly reduce the risk of burns. With high air permeability, fabrics breathe, keeping the wearer more comfortable.

Westex® by Milliken® fabric is UL Certified to NFPA 2112, CAN/CGSB-155.20, NFPA 1975 (7 oz only), NFPA 1977 and Arc Rated according to ASTM F1506 for NFPA 70E as HRC/CAT 2.

Westex® CXP® Nomex® Flame Resistant Fabric

Westex® CXP® is a patented, flame-resistant fabric made of DuPont™ Nomex® IIIA. The fabric is more comfortable and lasts longer than comparable Nomex® fabrics, and is the best choice for protective industrial uniforms and for fire service.

Milliken®'s Softouch Technology® ensures that Westex® CXP® is soft to the touch and has improved airflow through the fabric and the proprietary Visa® technology provides superior wicking for moisture management and helps oily stains wash out. Plus, Westex® CXP® is 40% lighter than FR Cotton/Nylon 9 oz. fabrics, an important factor in overall comfort. All of this keeps you cool and dry while working in hot environments.

Westex® CXP® fabric is UL Certified to NFPA 2112, CAN/CGSB-155.20 (155.22), NFPA 1975, NFPA 1977 and Arc Rated according to ASTM F1506 for NFPA 70E as HRC/CAT 1.

Milliken® DuPont™ Nomex® CXP® HRC 2 Inherent Flame Resistant Fabric

Nomex® CXP® fabric by Milliken® was specifically developed to provide improved comfort with dual-hazard fire and electric arc protection. This uniquely made fabric also offers the proven durability, life cycle value and inherent flame resistance that you have come to expect from Nomex®.

Nomex® CXP® is a patented, inherently flame-resistant fabric innovation that helps protect against both fire and electric arc flash hazards. This dual-hazard solution combines proprietary technology engineered by Milliken® to enhance arc protection for DuPont™ Nomex®—which is recognized as a leading flame-resistant (FR) fabric for fire protection in oil and gas, military, emergency response and automobile racing applications.

Nomex® CXP® is UL Certified to NFPA 2112, CAN/CGSB-155.20 (155.22), NFPA 1975, NFPA 1977 and Arc Rated according to ASTM F1506 for NFPA 70E as HRC/CAT2.

Viking® Firewall FR® products offer superior safety performance, improved comfort and durability, and best value in FR safety workwear



- Flame-resistant hook-and-loop closures
- Fully stitched bi-swing back to provide more comfort and mobility
- All seams are sewn with 100% flame-resistant Nomex[x] thread
- Use only high YKK® flame-resistant zippers
- All metal is thermally protected from the skin
- All stress points are bar tacked to offer ultimate durability
- Industrial wash 3M™ Scotchlite™ Retroreflective trim with flame-resistant backing

Viking® Firewall FR® Button Front Shirt

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 7 oz. Westex® by Milliken® flame-resistant fabric – 88% cotton/ 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2 (HRC 2)
- Button front closure with full-length placket with a button-down collar
- Full sleeves with adjustable button cuffs
- 2 chest pockets with button closure and box pleat on back
- Dual hazard protection from electrical arc and hydrocarbon flash fire



Size SR - 4XLT

WESTEX® by Milliken

31B77

1100 Dark Navy

1800 Light Blue

Viking® Firewall FR® Cargo Pants

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 9 oz. Westex® by Milliken® flame-resistant fabric – 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2 (HRC 2)
- All brass closures thermally protected from the skin
- Dual hazard protection from electrical arc and hydrocarbon flash fire
- Cargo style work pants
- Reinforced front slant pockets and back seat pockets
- Generous sized side pockets with flaps, and hook-and-loop closure
- Belt loops, metal button waist closure and Nomex® backed YKK® zipper fly



Size 30 - 48

WESTEX® by Milliken

20179

1100 Dark Navy



40577

1200 Royal Blue

40579

1100 Dark Navy

1200 Royal Blue

Viking® Firewall FR® Striped Coveralls

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- "Oil Patch" style reflective striping configuration
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame resistant trim (2" yellow/silver/yellow) with X on back and stripes around each forearm and each leg below the knee
- Two-way breakaway Nomex® backed YKK® front zipper
- Adjustable cuffs, tunnel collar with hook-and-loop closure
- 2 front upper pockets (including 1 mesh gas monitor pocket), and 2 lower front pouch pockets with side access vents
- 1 tool pocket on rear right leg, and 1 left sleeve pencil pocket
- Elasticized waist on the back and fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire

405791200 available in XSR - 5XLT

Size SR - 5XLT

3M Scotchlite WESTEX by Milliken

40577 Viking® Firewall FR® Striped Coveralls 7 oz.

- 7 oz. Westex by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2 (HRC 2)

40579 Viking® Firewall FR® Striped Coveralls 9 oz.

- 9 oz. Westex by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2 (HRC 2)



40477
40478
40479

5400 Orange

Viking® Firewall FR® CSA High Visibility FR Coveralls

- Fully compliant with CSA Z96-15 Class 3, level 2
- Meets WCB/Worksafe BC/DOT configuration
- RT80 featuring 3M Scotchlite™ Reflective Material–9740 industrial wash flame-resistant trim (4" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper, adjustable cuffs, tunnel collar with hook-and-loop closure
- 2 front upper pockets (including 1 mesh gas monitor pocket), and 2 lower front pouch pockets with side access vents
- 2 chest straps
- 1 tool pocket on rear right leg, and 1 left sleeve pencil pocket
- Elasticized waist on the back and fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire

40479 available in SR - 5XLT

Size SR - 4XLR

3M Scotchlite WESTEX by Milliken

40477 Viking® Firewall FR® CSA High Visibility FR Coveralls 7 oz.

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 7 oz. Westex by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2

40478 Viking® Firewall FR® CSA High Visibility FR Coveralls 7 oz.

- Same as 40477
- 15" Nomex® backed YKK® leg zipper

40479 Viking® Firewall FR® CSA High Visibility FR Coveralls 9 oz.

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 9 oz. Westex by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2 (HRC 2)

Viking® Firewall FR® CSA Striped Coveralls

- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame resistant trim (2" yellow/silver/yellow). CSA Z96-15 Class 1, Level FR striping pattern.
- Two-way breakaway Nomex® backed YKK® front zipper
- Adjustable cuffs, tunnel collar with hook-and-loop closure
- 2 front upper pockets (including 1 mesh gas monitor pocket), and 2 lower front pouch pockets with side access vents
- 2 chest straps
- One tool pocket on rear right leg, one left sleeve pencil pocket
- Elasticized waist on the back and fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire

1100 and 1200 available in XSR - 5XLR; 5400 available in SR - 4XLR

Size SR - 5XLR

3M Scotchlite™ WESTEX® by Milliken

40677 Viking® Firewall FR® CSA Striped Coveralls 7 oz.

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 1, Level FR.
- High visibility orange (5400) complies with CSA Z96-15 Class 3, Level FR
- 7 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2 (HRC 2)

40679 Viking® Firewall FR® CSA Striped Coveralls 9 oz.

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 3, Level FR
- 9 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2 (HRC 2)



40677

- 1100 Dark Navy
- 1200 Royal Blue
- 5400 Orange

40679

- 5400 Orange

Viking® Firewall FR® Miner 49er Mining Coveralls

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 3, Level 2
- 2" Vi-brance® flame-resistant industrial wash reflective tape
- 7 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2 (HRC 2)
- Two-way breakaway Nomex® backed YKK® front zipper
- Adjustable cuffs, tunnel collar with snap closure
- 2 front upper pockets, and 2 lower front pouch pockets
- Fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire



VC49

Size S - 4XL

WESTEX® by Milliken — Vi-brance® FR Reflective Material Matériel Réfléchissant



Viking® Firewall FR® CXP® Nomex® CSA Striped Coveralls

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 (Class 1/Level FR)
- 5.8 oz. DuPont® CXP® HRC2 Nomex® IIIA
- TPP Value: Contact 7.9, Spaced 13.5
- ARC rating ATPV: 10.2 cal/cm² CAT 2 (HRC 2)
- RT80 featuring 3M Scotchlite™ Reflective Material–9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper
- Adjustable cuffs, tunnel collar with hook-and-loop closure
- 2 front upper pockets (including 1 mesh gas monitor pocket), and 2 lower front pouch pockets with side access vents
- 1 tool pocket on rear right leg, and 1 left sleeve pencil pocket
- Elasticized waist on the back and fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire

40665

1200 Royal Blue

Size SR - 3XLT



Viking® Firewall FR® CXP® Nomex® IIIA CSA Striped Bib Overalls

- Meets safety standards: PPE Category 1, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 (Class 1/Level FR)
- 5.8 oz. DuPont® CXP® HRC2 Nomex® IIIA
- TPP Value: Contact 7.9, Spaced 13.5
- ARC rating ATPV: 10.2 cal/cm² CAT 2 (HRC 2)
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper with exterior storm flap closure
- Shoulder suspenders with adjustable buckles
- 2 front upper chest pockets, 2 large back pockets, and 2 lower front patch pockets
- Right tool pocket and hammer loop on left rear
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire

41666

1200 Royal Blue

Size S - 5XL

Viking® Firewall FR® CSA Striped Bib Overalls

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 1, Level FR.
- High visibility orange (5400) complies with CSA Z96-15 Class 2, Level FR
- 9 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2 (JRC 3)
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper with exterior storm flap closure
- Shoulder suspenders with adjustable buckles
- 2 front upper chest pockets, 2 large back pockets, and 2 lower front patch pockets
- Right tool pocket and hammer loop on left rear
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire



41679

- 1100 Dark Navy
- 1200 Royal Blue
- 5400 Orange

Size S - 5XL

3M Scotchlite™ WESTEX® by Milliken

Viking® Firewall FR® CXP® Nomex® Striped Insulated Overalls

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 5.8 oz. DuPont® CXP® HRC2 Nomex® IIIA (outer shell)
- 12 oz. quilted modacrylic lining with wind and vapor barrier
- TPP Value: Contact 7.9, Spaced 13.5
- ARC rating ATPV: 32 cal/cm² CAT 3 (HRC 3)
- RT80 featuring 3M Scotchlite™ Reflective Material–9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)-striping around lower legs
- Easy boot access with 15.5" Nomex® backed YKK® leg zippers
- Elastic shoulder suspenders with adjustable buckles
- 1 upper pocket with closure and pencil slot, 2 rear patch pockets, 2 lower front patch pockets, 1 right tool pocket
- Double knees and elastic waistband
- Dual hazard protection from electrical arc and hydrocarbon flash fire



51566

- 1200 Royal Blue

Size S - 4XL

3M Scotchlite™ DuPont™ Nomex® CXP® Milliken® HRC 2 Inherent FR Fabric



Viking® Firewall FR® Striped Insulated Overalls

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 9 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon (outer shell)
- 12 oz. quilted modacrylic lining with wind and vapor barrier
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 35 cal/cm² CAT 3 (HRC 3)
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame resistant trim (2" yellow/silver/yellow) – striping around lower legs.
- Nomex® backed YKK® two-way breakaway front zipper with exterior storm flap closure
- Easy boot access with 15.5" Nomex® backed YKK® leg zippers
- Elastic shoulder suspenders with adjustable buckles
- 1 upper pocket with closure and pencil slot, 2 rear patch pockets, 2 lower front patch pockets, 1 right tool pocket
- Double knees and elastic waistband
- Dual hazard protection from electrical arc and hydrocarbon flash fire

51579

1100 Dark Navy

1200 Royal Blue

Size XS - 5XL

3M Scotchlite™ WESTEX® by Milliken



Viking® Firewall FR® Striped Insulated Overalls

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 2/Level FR
- 9 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon (outer shell)
- 12 oz. quilted modacrylic lining with wind and vapor barrier
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 35 cal/cm² CAT 3 (HRC 3)
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame resistant trim (2" yellow/silver/yellow)
- Nomex® backed YKK® Two-way breakaway front zipper with exterior storm flap closure
- Easy boot access with 15.5" Nomex® backed YKK® leg zippers
- Elastic shoulder suspenders with adjustable buckles
- 2 rear patch pockets, 2 lower front patch pockets, 1 right tool pocket
- Double knees and elastic waistband
- Dual hazard protection from electrical arc and hydrocarbon flash fire

51679

5400 Orange

Size M - 4XL

3M Scotchlite™ WESTEX® by Milliken

Viking® Firewall FR® CSA Striped Insulated Parka

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70-2015, OSHA 1910.269, CSA Z96-15 Class 1/Level FR
- High visibility orange (5400) is compliant with CSA Z96-15 Class 2/Level FR
- 9 oz. Westex® by Milliken® flame-resistant fabric - 88% cotton / 12% nylon (outer shell)
- 12 oz. Quilted modacrylic lining with wind and vapour barrier
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 35 cal/cm² CAT 3 (HRC3)
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper with exterior storm flap closure
- Tunnel collar with closure
- 2 large upper chest pockets (including 1 mesh gas monitor pocket), 2 oversized lower front patch pockets with closure flaps and side entry hand warmer pockets with FR fleece pocket lining
- Left sleeve pencil pocket and 1 left inside pocket
- 2 chest straps
- Bi-swing back with elasticized waistband and drawstring with cord locks
- FR storm cuffs
- Snap-on hard hat hood sold separately (68G79)
- Dual hazard protection from electrical arc and hydrocarbon flash fire



55679

- 1100 Dark Navy
- 1200 Royal Blue
- 5400 Orange

5400 available in SR - 4XLR

Size XSR - 5XLT

3M Scotchlite™ WESTEX® by Milliken

Viking® Firewall FR® CXP® Nomex® Striped Insulated Parka

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 5.8 oz. DuPont® CXP® HRC2 Nomex® IIIA (outer shell)
- 12 oz. Quilted modacrylic lining with wind and vapour barrier
- TPP Value: Contact 7.9, Spaced 13.5
- ARC rating ATPV: 32 cal/cm² CAT 3 (HRC 3)
- RT80 featuring 3M Scotchlite™ Reflective Material – 9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper with exterior storm flap closure
- Tunnel collar with closure
- 2 large upper pockets (including 1 mesh gas monitor pocket), 2 lower front patch pockets with closure flaps and side entry
- Left sleeve pencil pocket, and 1 left inside pocket
- 2 chest straps
- Bi-swing back with elasticized waistband and drawstring with cord locks
- FR storm cuffs, thread, and tape
- Dual hazard protection from electrical arc and hydrocarbon flash fire



55566

- 1200 Royal Blue

Size SR - 5XLR

3M Scotchlite™ DuPont™ Nomex® CXP® Milliken® HRC 2 Inherent FR Fabric

Viking® Firewall FR® Hard Hat Winter Hood



- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 9 oz. Westex® by Milliken® Flame Resistant Fabric - 88% cotton/12% nylon (outer shell)
- 12 oz. Quilted modacrylic lining with wind and vapour barrier
- TPP Value: Contact: 10.3, Spaced 11.4
- ARC rating ATPV: 35cal/cm²
- CAT 3 (HRC 3)
- Front drawstring closure with cord locks
- FR hook-and-loop closing storm flap face protector
- Snap onto Style 55679 parka, and 55566 insulated parka

68G79

- 1100 Dark Navy
- 1200 Royal Blue
- 5400 Orange

Size: Fits all

WESTEX® by Milliken

Nomex® IIIA Knit Toque



- Meets safety standards: CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- Nomex® IIIA knit fabric
- Double thick knit construction
- Flat seaming for comfort

62F00

- 1000 Black

Size: Fits all

DuPont™ Nomex®

Viking® Firewall FR® Ankle Guard



- Meets safety standards: PPE Category 2, CGSB 155.20-2000, CSA Z462-18, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 9 oz. Westex® by Milliken® Flame Resistant Fabric - 88% cotton/12% nylon blend
- TPP Value: Contact: 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2
- 2 layers of fabric
- Hook and loop closure

6T779

- 1200 Royal Blue

Size: Fits all

WESTEX® by Milliken