SLAP SHOT PL Low VOC™

DESCRIPTION

SLAP SHOT PL Low VOC™ is specially formulated to effectively dissolve and remove grease, oil and other contaminants where plastics and rubber-like compounds are present.

- Quick acting
- Penetrates and displaces moisture
- Effectively cuts through and removes grease, oil, paint, ink, glue, adhesive, wax, dirt and grime
- Safe on plastics and rubber-like compounds
- Low VOC formula
- Free of chlorinated solvents, CFC and HCFC
- Aerosol: strong jet blasts away contaminants

APPLICATIONS

Use SLAP SHOT PL Low VOC™ for:

- Cleaning of metal parts in the presence of plastic or gaskets
- Maintenance, repair and overhaul of motors, machinery, vehicles and equipment
- Removal of glue, paint, ink, resin, sealant and flux residue
- Cleaning of electric components, instruments, lenses, glass, chains, gears, cables, etc…

RECOMMENDATIONS FOR USE

- Spray directly on parts

TECHNICAL DATA

Physical state: Aerosol
Density: 0.78 g/mL (20°C/ 68°F)
VOC: 9.5% (w/w)
Flash point: 24°C (72.5°F)
Auto ignition temperature: 175 °C (347°F) ASTM E659
Engineering controls: Ensure adequate ventilation
Storage: Store in cool, dry, well-ventilated areas away from heat, direct sunlight and strong oxidizers
Shelf life: 2 years in closed container, stored in ideal conditions

ORDERING INFORMATION

Description	Size	Order No.	(M)SDS
Aerosol	450ml	53-C 552	L-214 E

(M) SDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice.

Walter Surface Technologies Inc.
5977 Trans-Canada Highway, Pointe-Claire, Quebec H9R 1C1
Tel: 1-800-592-5837 or (514)630-2800 / Fax: (514)630-2825